# Dump Truck Safety on the Roadway

### 1.5 Seconds

Maximum time eyes away from forward roadway to check mirrors, etc.



## **Following Distance**

## Over 40 mph = **Minimum Five** Seconds<sup>1</sup>

Increase distance further for driving:

- Tractor-trailer combinations
- At night
- During inclement weather



# It's not worth it.



#### Speed

Speed limits are designed for light vehicles with better handling capabilities than a dump tuck. Obey speed limits and drive under the speed limit when turning or going into sharp turns and ramps. Reduce your speed during inclement weather.




70%

**Protect** yourself!

At 70%, dump truck drivers have the **lowest** seatbelt usage rate.<sup>2</sup>



To other drivers, larger vehicles appear to be moving slower. Anticipate unsafe actions of others, like pulling out in front of you.





#### **Prevent Falling Debris**

Keep loads at least six inches below sides. Brush off loose materials and tarp when required.<sup>3</sup>



www.fmcsa.dot.gov/safety/driver-safety/cmv-driving-tips-following-too-closely



<sup>&</sup>lt;sup>2</sup> Federal Motor Carrier Safety Administration, Commercial Motor Vehicle Safety Belt Facts, March 2014


<sup>&</sup>lt;sup>3</sup> Guide to Commercial Vehicle Covering and Cargo Control Laws, Tarp Association, © 2015 Industrial Fabrics Association International.

# **Unloading Accidents**

Be very cautious. Do not unload in heavy winds.




Tipping occurs when the center of gravity moves as the bed is raised.




Unload on flat stable ground. Slopes or unstable ground can create major shifts in the center of gravity and rollovers.

When loading, distribute loads






After dumping load, lower bed before moving.



evenly.











When dumping, line trailers, tractors and wheels up straight.

Review your truck/trailer operator's manual for specific unloading safety procedures. Conduct thorough pre- and post-trip inspections. Equipment failure causes rollovers.

The dump truck back-over fatality rate is **68% higher** than any other commercial vehicle.4

Get Out And Look!



#### Always check above!

Truck contact with power lines is the 4th leading cause of electrocution deaths in construction.5



Occupational Safety and Health Administration, osha.gov/preventing-backovers, OSHA Integrated Management Information System data, 2005-2010.

The information used to create this brochure was obtained from sources believed to be reliable. Nationwide, its affiliates and employees do not guarantee improved results based upon the information contained herein and assume no liability in connection with the information or the provided safety suggestions. The recommendations provided are general in nature; unique circumstances may not warrant or require implementation of some or all of the safety suggestions. There may be additional available safety procedures that are not referenced in this brochure. Nationwide, Nationwide is on your side, and the Nationwide N and Eagle are service marks of Nationwide Mutual Insurance Company. © 2021 Nationwide